## 5 Hole Triple Handle Wall Mount Bathtub Faucet Color Changing LED Lights Chrome Finish Brass Body



## **INSTALLATION INSTRUCTIONS**

## INSTALLATION INSTRUCTIONS

- Install the rough-in valve body behind the finished wall. Attach the valve body to wood blocking between two
  wall studs with wood screws. Be sure that the rough-in valve is completely level, and connect to the main water
  supply.
- When the wall around the rough-in valve is finished, install your faucet trim.
- If your faucet spout is not assembled, assemble by connecting the threaded outlet to the faucet body. If your spout is already assembled move on to the next step.
- 4. If your faucet features a decorative face plate, secure the face plate to the wall with silicone sealant before installing your handle and spout trim pieces. Make sure that the face plate is properly aligned over the rough-in valve and perfectly straight. If your faucet does not feature a face plate move on to the next step.
- 5. If the decorative spout escutcheon is not attached, place the escutcheon on the body of the spout and install the spout over the spout shank. Screw the spout into place and press the escutcheon firmly against the finished wall.
- Tighten any set screws in the spout with an Allen wrench.

   Install the bandle/s) and any assessment bandware and tight.
- 7. Install the handle(s) and any necessary hardware and tighten the set screws with your Allen wrench. If rubber O-rings or sealing gaskets are included, place between the handle body and wall to create a water tight seal.
- 8. When your faucet installation is complete, turn on the water supply. Check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the water on and allow the water to flow through the spout for approximately 60 seconds.



